



Pressure Sensitive Adhesive For Installations of Knight Quartz Concepts and Knight QuartzScapes

4 GALLONS
15.14 L

For complete warranty details contact Customer Support at 866-850-8836

Use For:

For installations of Knight Quartz Concepts and Knight QuartzScapes

Bonds To:

Porous

Recommended over suspended wood floor, certain underlayment boards approved by the flooring manufacturer, cementitious underlayments, and dry concrete that is above, on or below grade where there is less than 5lbs/1000 sq. ft./24 hours as determined by the calcium chloride moisture test (ASTMF-1869).

Non-porous

Terrazzo, ceramic tile, metal, existing fully adhered non-cushion backed resilient on all grade levels except existing tile below grade.

Preparation:

- ◆ Read installation instructions thoroughly prior to installation.
- ◆ Store flooring and adhesive conditioning the area to be installed at a temperature of 65°F (18°C) 48 hours before, during and after installation
- ◆ All surfaces must be clean, dry and free of dust, grease, paints, oils, sealers and curing compounds or any other foreign materials which may interfere with proper adhesion.

Installation:

- ◆ Spread adhesive with a 1/16"D x 1/16"W x 1/16"A Square-notch trowel. Allow adhesive to dry to the touch (approximately 30 - 45 minutes). Install flooring within 24 hours.
- ◆ Roll flooring material with a 75 - 100 lb. roller across width and length.
- ◆ Avoid traffic within 12 hours of installation.

Clean Up:

Remove wet adhesive residue using a clean, white cloth dampened with soapy water. Use mineral spirits for dried adhesive residue carefully following warnings on container.


CAUTION: EYE AND SKIN IRRITANT. Avoid eye and skin contact. If eye contact occurs, flush with water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Keep container closed. **KEEP OUT OF REACH OF CHILDREN.**

NOTE: Do not reuse container. Dispose of container and adhesive residue in accordance with federal, state and local waste disposal regulations. Do not flush adhesive down drains.

- ◆ **Shelf Life:** one year if not opened.
- ◆ **VOC Content:** 0 g/L, calculated, SCAQMD 1168

Manufactured in the U.S.A. by The W.W. Henry Co. for Knight Premium Flooring.

Trowel Recommendations and Coverage



1/16" D x 1/16" W x 1/16" A Sq-Notch Trowel
Approx. 130 sq. ft./gal.

