



Wet Set Adhesive For Installations of Knight Quartz Concepts and Knight QuartzScapes

4 GALLONS
15.14 L

For complete warranty details contact Customer Support at 866-850-8836

Use For:

For installations of Knight Quartz Concepts and Knight QuartzScapes

Bonds To:

Porous

Recommended over suspended APA approved wood, underlayment board, cementitious underlayments, dry concrete that is above, on or below grade where there is less than 3lbs/1000 sqft/24 hours as determined by the calcium chloride moisture test (ASTM-F-1869).

Non-porous

Staircases, terrazzo, ceramic tile, metal, existing fully adhered non-cushion backed resilient on all grade levels and poured polymeric floors.

Preparation:

- ◆ Read installation instructions and MSDS thoroughly prior to installation.
- ◆ Store flooring and adhesive conditioning the area to be installed at a temperature of 65°F (18°C) 48 hours before, during and after installation
- ◆ All surfaces must be clean, dry and free of dust, grease, paints, oils, sealers and curing compounds or any other foreign materials which may interfere with proper adhesion.

Installation:

Porous substrates

- ◆ Spread adhesive evenly on the surface with a 1/16"x 1/16"x 1/16" Square-notched trowel. Allow the spread adhesive to remain open about 15-25 minutes. Working time over concrete, up to 90 minutes depending on temperature and humidity during installation. Roll flooring material with a 75-100 lb. roller across width and length.

Trowel Recommendations and Coverage



Porous substrates:
1/16" D x 1/16" W x 1/16" A Sq-Notch Trowel
Approx. 125 sq. ft./gal.



Non-porous substrates:
1/32" D x 1/16" W x 5/64" A U-Notch Trowel
Approx. 160 sq. ft./gal.

Non-porous substrates

- ◆ Spread adhesive evenly on substrate using a 1/32"Dx1/16"Wx5/64"A U-notch trowel. Allow adhesive to dry for approximately 30-40 minutes, depending on temperature and humidity conditions. Working time up to 2 hours, depending on temperature and humidity conditions. Roll flooring material with a 75-100 lb. roller across width and length.
- ◆ Avoid traffic within 12 hours of installation.

Clean Up:

Remove wet adhesive residue using a clean, white cloth dampened with soapy water. Use mineral spirits for dried adhesive residue carefully following warnings on container.

WARNING: EYE AND SKIN IRRITANT. Contains glycol ethers. Avoid eye and skin contact. If eye contact occurs, flush with water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Keep container closed. **KEEP OUT OF REACH OF CHILDREN.**

NOTE: Do not reuse container. Dispose of container and adhesive residue in accordance with federal, state and local waste disposal regulations. Do not flush adhesive down drains.

- ◆ **Freeze thaw:** Protect from freezing
- ◆ **Shelf Life:** Store the adhesive in room between 40° F and 90° F. One year if not opened.
- ◆ **VOC Content:** 4 grams/liter

Manufactured in the U.S.A. by The W.W. Henry Co. for Knight Premium Flooring.

